



DISAB SkipVAC™

Usage

DISAB SkipVAC™ is a powerful and compact suction unit, designed to vacuum material and dust in industrial environments where the demands for efficient and reliable equipment are high. The unit is equipped with its own skip, which is handled by a fork lift and powered by electric supply.

The DISAB SkipVAC™ is incredibly versatile and can be used across a wide range of industries and settings including manufacturers of cement, lime, gypsum, tiles, concrete, chemicals, steel mills, bakeries etc

Description

Its small footprint and quiet operating levels means it's favorable by a wide range of industries that also appreciate its flexibility, ease of use and robustness. The combined power pack and filter assembly is mounted on top of a self-tipping skip, so the unit can easily be lifted and transported to wherever collected debris needs to be disposed, or cleaning needs to be carried out. The unit is fully enclosed so dust is safely contained and it comes with flexible hoses and specially designed attachments that enables complete access to hard to reach areas.

Benefits

The high suction capacity together with the large collecting capacity makes DISAB SkipVAC™ very useful in most cleaning situations.

Other benefits include:

- Fitted with forklift sleeves for an easy transportation
- Removes anything from microscopic dust up to 40 mm debris
- Operated via a standard 32 amp 3 phase power supply
- Waste collected into integral skip for easy disposal or recycling
- Self-tipping bin for easy discharge
- Suction distances up to 100 meters
- Suction capacities up to 4 tons per hour
- Exceptional filtration levels, including optional HEPA filters
- Easy to operate
- Quiet in operation
- Can be used for powering fixed pipework vacuum systems around multi-level sites
- No dust valves or other moving parts involved, securing high availability factor and low maintenance costs.

Technical Data Chart for DISAB SkipVAC™

Description

Vacuum pump	Side channel blower (turbo)	Max vacuum, mbar	290
Air volume m³/h (unloaded)	1,100	Electrical Motor, kW	12.5
Tank volume (m³)*	1	Total Tank Volume (m³)	1.5
Discharge	Self tipping bin	Noise Level dB(A) (at 1m/5 m distance)	75/70
Filter surface (m²)	5	Fuse A	32


* Excluding filter volume

Miscellaneous

Hose connect (diameter, mm)	108	Filter Class	L, M IEC EN 60335-2-69
Material	Steel S 235 JG2	Painting	Class C2, color RAL 3003 red

Weight and Dimensions

A x B x C x D (mm)	1,750 x 1,390 x 1,680 x 1,100
Weight, kg (approx)	910



Easy to move, easy to use, easy to place. Thanks to the user-friendly design it is easy to move, empty and use the DISAB SkipVAC™.

DISAB SkipVAC™ suction unit meets the high demands from the industry due to its efficiency, reliability, ease of operation and maintenance giving excellent value for money.